

正面---

4K HD DP KVM Switch

User manual

Introduction

This DP KVM switch supports 4K high-definition resolution and 144Hz high refresh rate, ensuring clear and smooth gaming and entertainment without lagging. Realize the simultaneous connection of 2/4 DP input devices, sharing a set of keyboard, mouse, and monitor. The USB 3.0 HUB function supports 2/4 computers sharing a printer, USB flash drive, and other USB devices. It supports panel buttons and desktop controllers to quickly switch input sources, avoiding repeated cable plugging and unplugging, saving a lot of time and capital costs, and returning office and entertainment to the essence of ease and convenience.

Feature

- Support 4K@144Hz High resolution and high refresh rate
- Support 2/4 computers to share one set of keyboard, mouse, and monitor
- Supports multiple USB 3.0 devices such as shared printers
- 32.4Gbps high bandwidth, smooth and seamless signal transmission
- Supports switching between panel buttons and desktop controllers
- LED constant light signal indicator, check and detect port operation without misjudgment
- Compatible with domestic systems, WINDOWS full series, Linux, Mac and other systems

Packing List

2 port

2-port DP KVM Switch x 1

USB-A to C charging cable x1

USB-C data cable x 2

1.5-meter desktop controller x1

Foot pad x 1

User manual x 1

4 port

4-port DP KVM Switch x 1

USB-A to C charging cable x1

USB-C data cable x4

1.5-meter desktop controller x1

Foot pad x 1

User manual x 1

Interface

2 port front panel interface description

2 port rear panel interface description

4 port front panel interface description

4 port rear panel interface description

-1-

-2-

-3-

-4-

-5-

反面---

Connection Diagram

2 port

4 port

Instructions

Power on default port 1, both power supply and USB cable can be powered, USB signal follows the current selected port

Panel Key Switching

Tap the KVM switching digital buttons to select the corresponding DP IN port signal source display, the indicator follows the channel, and the USB signal follows the currently selected port.

2 port

4 port

Desktop Controller Switching

Connect one end of the 1.5 meter MINI USB 5P male-to-male cable to the KVM and the other end to the desktop controller (no distinction between positive and negative). Then press the center button of the desktop controller to switch the corresponding DP IN port source display, the indicator light follows the channel, and the USB signal follows the currently selected port.

2 port

4 port

Specification

Model	2 port / 4 port
Resolution	4K@144Hz and down-scaling
DP version	DP 1.4
Bandwidths	32.4Gbps
USB protocol	USB 3.0
USB port	4
Compatible system	Windows series, Mac os, Linux, etc.
Hot swapping	Support
Switching method	Panel pushbuttons, desktop controllers
Power supply	5V1A (With Type-C Cable)
Indicator status	Blue light always on
Shell material	Metal

Tips:
The illustrations of products and accessories in this manual are schematic diagrams. Due to product upgrades, the actual product may differ slightly from the schematic diagram. Please refer to the actual product.

-6-

-7-

-8-

-9-

-10-

单页75x105mm