

正面---

8K HDMI®2.1 Switch 2 in 1 out

USER MANUAL

Packing List




8K HDMI®2.1 Switch 2 in 1 out



User Manual × 1

-1-

Product Diagram



HDMI® input port

Indicator

HDMI® output port

Power port

HDMI®

The Adopted Trademarks HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries. OR *The terms HDMI, HDMI High-Definition Multimedia interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.*

-2-

反面---

Product Introduction


This 8K HDMI®2.1 switch supports 8K@60Hz resolution and 4K@120Hz high brush, which can realize two computers to share one display, support the use of panel key to quickly switch the source, enjoy ultra -high -definition picture quality, while enjoying the quality of ultra -high -definition picture quality, effectively save display resources, and easily cope with the use scenarios with high demand for picture studios and office teaching.

Product Feature

- Support 8K@60Hz resolution
- Support 4K@120Hz E -sports high brush
- Support two computers to share one display
- HDMI® input supply power, support external power
- HDMI® 2.1 downward compatible, Bandwidth 48Gbps
- Support 8 level gain adjustment and have memory functions

-3-

Connection Diagram



Tip:
You need to connect the standard HDMI2.1 cable to enjoy 8K visual effects. If you want to output 8K@60Hz, 4K@120Hz, make sure your signal source equipment, cable and display can support your required resolution and refresh rate, and then connect to use.

-4-

Gain adjustment method

Long press switch button to regulate the current HDMI channel. Each channel can be adjusted and memorized independently. From level 0 to level 7, it is divided into 8 levels. By the time of level 7, return to level 0 and circulate back and forth.

Before power - on, check whether the connection cable is normal carefully, it is necessary to ensure that all interfaces are connected normally. The common fault judgment and processing methods are as follows:

Fault phenomenon	Causes and solutions
No image	1. Confirm that the TV is turned on and connected to this unit. 2. Whether the input signal source is turned on and connected well. 3. Check whether the connection line is in good condition. 4. Check the connection status of the system.
image is blurred	1. Reconnect the connection port to prevent poor contact of the socket interface. 2. cable quality(HDMI® cable requirements comply with HDMI® standards)

-5-

单页55x70mm