

正面---

HDMI SWITCH

3 Port
5 Port

Product Introduction

This is HDMI 3/5 port switcher, supporting 3/5 devices to share one TV/monitor, allowing for free picture switching and maximizing efficiency. Up to 3840X2160@30Hz, 4K realm, within reach; Different devices can be switched through infrared remote control or buttons, which is convenient and fast. The product is compact and exquisite, plug-and-play without a driver, easy to operate and quick to install

Packing List

Name	Type
3-port HDMI Switch / 5-port HDMI Switch	1
IR Remote	1
Power line	1
User Manual	1

Features

- 3/5 signal sources can be switched at random
- Resolution supports 3840X2160@30Hz, downward compatibility
- Dual switching between infrared remote control and panel buttons ensures rapid response and convenient, efficient operation.
- Automatically identify the access signal and prioritize the jump. When the cable is unplugged, it will automatically return to the port displayed last time, making it more worry-free and intelligent.
- Compatible with Windows full range, Mac OS, Linux and other systems

Product model and information

3 Port

Front Panel

Side Panel

5 Port

Front Panel

Side Panel

Gain adjustment

Long press the switch button for 3 seconds :
Can adjust the output display screen by changing the gain

反面---

Connection diagram

3 Port

5 Port

Interface signal detection function

When any signal input is connected, the signal will immediately jump to display the port display (priority display for later connections).
Restart or unplug the current display port, and the signal will jump back to the last displayed port

IR Remote Switching

3/5 signal input sources correspond to remote control buttons 1-3/5.

3 Port

5 Port

Tip: Buttons without instructions are invalid

Parameters

Input Port	3*HDMI	5*HDMI
HDMI Output	1*HDMI	
Support resolution	3840*2160@30HZ Backward Compatible	
Resolution	8K/60FPS, 8K/30FPS, 4K/144FPS, 4K/60FPS and backward compatibility	
3D Visual	Supports	
Theoretical bandwidth	2.5Gbps	
HDMI	HDMI 1.4	
Cable distance	1080P 60HZ/4K30HZ ≤ (5+10M)	
Suitable equipment (input)	Computer hosts,PS,disk drives notebook, hard disk recorders and other HDMI devices	
Suitable equipment (output)	Monitors,televisions and other devices that support HDMI input	
Compatible System	Compatible with domestic systems, Windows series, Mac OS, Linux and other systems	
Switching Method	Button switch,infrared remote control	
Electrostatic protection	±8KV(contact discharge)	
Input voltage	5V	
Power supply	DC5V/1A (standard Type-C power cord)	
Operation temperature	0°C-55 °C	
Storage temperature	-20°C-60°C	
Shell material	Iron shell	

单页90x125mm