



BI-DIRECTION DP SWITCH	Introduction: This Bi-direction manual DP switch can easily switch 2 roads HD signal to any HD display device or projector. At the same time, you can also split a HD signal to two monitors or the projector. Supports 3D, 4K. It is a item that supports high definition resolution. 4K high quality mini DP bidirectional switch. The equipment is mainly used in security center, data control center and information division, conference exhibition hall, school and enterprise training environment.	Features: 1. Transmit the two DP signal sources to a DP monitor or TV respectively; 2. Transmit one DP signal source to two DP monitors or TVs respectively; 3. The product has low power consumption and does not require a power supply. If there is insufficient power supply (flash screen, snowflakes...), please purchase an Android charging cable by yourself and supply power through USB; 4. Control mode: manual button electronic switch; 5. 2 LED display signal indicators; 6. 3 DP interfaces; 7. Simple installation and convenient operation; 8. Size: 5.5*5.5*2cm; 9. Shell material: ABS plastic;	Specification: <table><tr><td>Resolution:</td><td>4K 60Hz downward compatible</td></tr><tr><td>Video bandwidth:</td><td>up to 21.60 Gbit/s</td></tr><tr><td>Operating temperature:</td><td>0 degrees to 70 degrees</td></tr><tr><td>Storage temperature:</td><td>-10 degrees to 80 degrees</td></tr><tr><td>Operating humidity:</td><td>10% to 85% (non-condensing)</td></tr><tr><td>Storage humidity:</td><td>5% to 90% (non-condensing)</td></tr><tr><td>Additional power supply:</td><td>no additional power supply required</td></tr><tr><td>Power consumption:</td><td><1W</td></tr></table>	Resolution:	4K 60Hz downward compatible	Video bandwidth:	up to 21.60 Gbit/s	Operating temperature:	0 degrees to 70 degrees	Storage temperature:	-10 degrees to 80 degrees	Operating humidity:	10% to 85% (non-condensing)	Storage humidity:	5% to 90% (non-condensing)	Additional power supply:	no additional power supply required	Power consumption:	<1W	Package list: 2-way DP switch x 1 User Manual x 1 USB power cable 1.2m x 1 Connection diagram: 1 in 2 out  2 in 1 out 	Note: please operate the equipment according to the instructions to ensure a long period of use life 1.The equipment should be stored in a dry place, away from an environment that humidity, high temperature, dust, and prone to erosion and oxidation 2.Avoid all parts from being collided, shaking violently, falling, please don't open the shell and do not touch the internal parts.
	Resolution:	4K 60Hz downward compatible																			
Video bandwidth:	up to 21.60 Gbit/s																				
Operating temperature:	0 degrees to 70 degrees																				
Storage temperature:	-10 degrees to 80 degrees																				
Operating humidity:	10% to 85% (non-condensing)																				
Storage humidity:	5% to 90% (non-condensing)																				
Additional power supply:	no additional power supply required																				
Power consumption:	<1W																				
	1	2	3	4	5																