

Wireless Screen Cast Kits

User Manual

Connection Diagram

Receiver
To Monitor

switch

Indicator Light

3.5mm Jack

TYPE-C Power Supply Port

HDMI

VGA

HDMI Transmitter
To PC

Function Button

Indicator Light

Type-C power supply port

HDMI

TYPE C Transmitter
To PC

Function Button

Indicator Light

TYPE C

Hardware Casting

Combination of receiver and transmitter, plug and play

Take HDMI Transmitter as an example

1. Connect the HDMI port or VGA port of the receiver to the video input port of the display device such as the monitor or TV.

2. Connect the TYPE-C power supply port of the receiver to the charging cable and plug it into the power adapter (Voltage above 5V, current above 2A).

3. Adjust the HDMI signal source of the monitor or TV to the corresponding HDMI port until the boot screen is displayed.

4. Connect the transmitter to the computer or other devices with HDMI video output function. After the indicator light enters the fast flash state, wait for ten seconds to complete casting.

* Please make sure that the power of the computer is sufficient. If the power supply of the computer is insufficient or HDMI is unable to supply power, please connect the transmitter to the power adapter or USB power supply port (Voltage above 5V, current above 2A).

Pairing Instructions

The product has been paired out of the factory. In case of pairing failure due to improper operation or other circumstances during use, it is necessary to restore and re pair the device as follows:

Indicator Light

Transmitter - Function Button

Transmitter Indicator Status	
Slow Flash	Disconnected
Fast Flash	Pairing
Always ON	Connected

1. Please use the thimble to press in the small hole at the bottom of the receiver for 3-5 seconds, and the prompt will pop up on the interface: Release the button to pair with EZCast TX. Wait for the transmitter to enter pairing mode.

2. Press the transmitter function button for more than 3 seconds, the indicator will flash for pairing, and wait for the transmitter indicator to be always on, indicating that the connection is successful.

* With one receiver and multiple transmitters, 1 receiver can pair with 8 transmitters for switching.

Function Settings

1. Search for receiver in Wireless Network (Name is MT-VIKI-XXXX, default password is 12345678)

2. Open the mobile / tablet browser and enter 192.168.203.1 in the address bar

3. It can perform operations such as network distribution, resolution, portrait mode, upgrade and restart.

Software Casting

When the receiver is used alone, it needs to cooperate with the software in the mobile phone or computer

Complete the "Internet" distribution network in the Function Settings

Apple iOS System - Operation Steps

Slide the screen to enter the Apple Device Control Center, click Airplay, and check the MT-VIKI device.

Android System - Operation Steps

1. Turn on the screen casting function in the mobile phone / tablet

2. Search and connect to MT-VIKI device

Different brand screen casting function path reference

HUAWEI : Setting>Smart Assist>Multi-screen Interactive

Xiaomi:Settings>Connect and Share>Cast Screen

VIVO :Settings>Other connection methods>Smart screen

OPPO :Settings>Other connection methods>Smart screen

MEIZU : Settings>Display>Projection Screen

Lenovo : Setting>Display>Wireless Display

SAMSUNG : Phone From Top To Bottom>Smart View

Problem solving

Q: How to restore factory settings?

A: When the product fails, press and hold the receiver function button for 10 seconds. After a black screen appears and restart, the factory settings will be restored.

Q: Can devices without HDMI interface be used?

A: Yes, please use the device with an HDMI interface converter.

Q: How to enter privacy mode?

A: Tap the transmitter function button to disconnect or reconnect.